



120F0281 🗷

Reciprocating compressor, NTZ096A3LR1B

Refrigerants: R404A; R452A, Segment usage: Refrigeration LT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	37.5 Kg
Net weight	35 Kg
Volume	61.54 Liter
EAN	5702428665315
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	NTZ096-3B
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502012g
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	NTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 ℃
High Side TS Min	-35 °C



PRODUCT DETAILS	
High Side Volume	0.6 L
High value of nominal voltage at	230 V
60Hz [V]	250 (
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 ℃
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	72 A
Max pressure (PS) - high side	28.5 bar
Max pressure (PS) - low side	22.6 bar
MCC	20.4 A
Model number	NTZ096A3LR1B
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	450 mm
Packaging length [mm]	385 mm
Packaging width [mm]	375 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	NTZ
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R404A
	R452A
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Refrigeration LT
Shipped fittings	Suction and discharge solder sleeves,
	rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts,
	nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1 3/4 in



PRODUCT DETAILS

Swept volume [cm3]	96 cm ³	
Technology	Reciprocating	
Test Dif [bar] [Max]	30 bar	
Test HP [bar] [Max]	30 bar	
Test LP [bar] [Max]	25 bar	
Torque earth [Nm]	3 N-m	
Torque power [Nm]	3 N-m	
Total height [mm]	413 mm	
Туре	NTZ096	
UK RoHS compliance	Out of scope	
Viscosity [cP]	32 cP	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



120Z0763 🗷

Mounting, Compressor kit

Mounting kit 2 cylinder



8156132 🗷

Connector, GASKET

Gasket, 1-3/4"



8153008 🗷

Connector, Solder Sleeve

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)



8156134 🗷

Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp



120Z0576 🗷

Acoustic hood, Reciprocating

Acoustic hood for two-cylinder compressor



8156009 🗷

Connector, GASKET

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories



8153013 🗷

Connector, Solder Sleeve

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)



7750009 🗷

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8156131 🗷

Connector, GASKET

Gasket, 1-1/4"

Spare Parts



7773109 🗈

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 110 V, CE mark, UL



7703006 🗷

Connector, Valve set

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")



8156019 🗈

Connector, Sight glass

Oil sight glass with gaskets (black and white)



8156145 🗷

Connector, GASKET

Gasket for oil sight glass (black chloroprene)



8168032 🗷

Connector, Rotolock service valve

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)



120Z0638 🗷

Lubricant, 175PZ

POE lubricant, 175PZ, 1-litre can

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



8168029 🗷

Connector, Rotolock service valve

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)



7773107 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 230 V, CE mark, UL



120Z0459 🗷

Crankcase heater, PTC heater

PTC heater 27W, CE mark, UL