



MT18-3VI 🛛

Reciprocating compressor, MT18JA3NVE

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

| Gross weight | 23.88 Kg |
|-------------------------------------|--|
| Net weight | 22 Kg |
| Volume | 37.73 Liter |
| EAN | 5702428839846 |
| Approval | CE |
| | UL |
| | UKCA |
| Brand technique | Reciprocating compressor |
| Capacity control | Fixed speed |
| China RoHS compliance | Out of scope |
| Colour | Blue |
| Compressor power supply [V] | 200-230/3/60 |
| Configuration code | Single |
| Connection type | Rotolock |
| Cylinder | 1 |
| Description | MT018-3 |
| Diameter [mm] | 224 mm |
| Discharge connection height [mm] | 68 mm |
| Discharge connection pipe size [in] | 3/8 in |
| Discharge connection size [in] | 1 in |
| Drawing number | 8501024e |
| Economizer | No |
| EU RoHS compliance | Yes with exemptions |
| EU RoHS exemption clause | 6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b) |
| Factory HP [bar] | 25 bar |
| Factory LP [bar] | 25 bar |
| Family | MT |
| Fitting remark | (shipped with rotolock version only) |
| Fitting sleeve | ODF |
| Fitting standard | Rotolock |
| Frequency [Hz] | 60 |
| Gauge port HP | None |
| Gauge port LP | Schrader |
| Glass mounting | Threaded |
| Glass torque [Nm] | 50 N-m |
| GP LP torque [Nm] | 15 N-m |
| High Side TS Max | 150 °C |
| High Side TS Min | -35 °C |
| | |

Product Detail | Reciprocating compressor, MT18JA3NVE



PRODUCT DETAILS

| High Side Volume | 0.3 L |
|-------------------------------------|---------------------------------------|
| High value of nominal voltage at | 230 V |
| 60Hz [V] | |
| High value of voltage range at 60Hz | 253 V |
| [V] | |
| In scope of WEEE and contain | No |
| batteries | |
| IP protection class | IP55 (with cable gland) |
| Low Side TS Max | 50 °C |
| Low Side TS Min | -35 °C |
| Low Side Volume | 7.5 L |
| Low value of nominal voltage at | 200 V |
| 60Hz [V] | |
| Low value of voltage range at 60Hz | 180 V |
| [V] | |
| LRA | 38 A |
| Max pressure (PS) - high side | 29.4 bar |
| Max pressure (PS) - low side | 18.4 bar |
| MCC | 9.5 A |
| Model number | MT18JA3NVE |
| | |
| Motor protection | Internal overload protector 15 N-m |
| Mounting torque [Nm] | |
| Network power supply [V/Ph/Hz] | 208-230/3/60 |
| Number of starts per hour [Max] | 12 |
| Oil charge [L] | 0.95 L |
| Oil equalization | 3/8" flare SAE |
| Oil equalization torque [Nm] | 30 N-m |
| Oil reference | 160P |
| Packaging height [mm] | 385 mm |
| Packaging length [mm] | 330 mm |
| Packaging weight [Kg] | 24 kg |
| Packaging width [mm] | 295 mm |
| Packing format | Single pack |
| Packing quantity | 1 |
| Phase | 3 |
| Power connections | Spade |
| Product group | Hermetic compressors |
| Product Name Description | MT |
| REACH Candidate List substances | Lead (CAS no. 7439-92-1) |
| Refrigerant charge [kg] [Max] | 3 kg |
| Refrigerants | R22 |
| Rotational speed at 60Hz [rpm] | 3500 rpm |
| SCIP dossier no. | 5a332c1b-1d1b-4998-8115- |
| | d0929877ecb4 |
| Segment usage | Refrigeration MT |
| Shipped fittings | Suction and discharge solder sleeves, |
| | rotolock nuts, and gaskets |
| Shipped instructions | Installation instructions |
| Shipped mounting | Mounting kit with grommets, bolts, |
| 2 | nuts, sleeves and washers |
| Shipped oil | Initial oil charge |
| Suction connection height [mm] | 263 mm |
| | |



PRODUCT DETAILS

| Suction connection material | <u> </u> |
|-----------------------------------|----------------------------------|
| Suction connection pipe size [in] | 1/2 in |
| Suction connection size [in] | 1 in |
| Swept volume [cm3] | 30.23 cm ³ |
| Technology | Reciprocating |
| Test Dif [bar] [Max] | 30 bar |
| Test HP [bar] [Max] | 30 bar |
| Test LP [bar] [Max] | 25 bar |
| Torque earth [Nm] | 3 N-m |
| Torque power [Nm] | 3 N-m |
| Total height [mm] | 333 mm |
| Туре | MT018 |
| UK RoHS compliance | Out of scope |
| Viscosity [cP] | 32 cP |
| Winding resistance for three- | 2.58 Ohm |
| phase compressors with identical | |
| windings [Ohm] | |
| Proposition 65 | WARNING: Cancer and Reproductive |
| | Harm |
| | www.p65warnings.ca.gov |
| | |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖄

| cessories | |
|-----------|---|
| 2 | 120Z0760 🖻 |
| | Mounting, Compressor kit |
| 80 | Mounting kit 1 cylinder low |
| | 120Z0575 🖻 |
| | Acoustic hood, Reciprocating |
| | Acoustic hood for one-cylinder compressor |
| | 8156009 ⊵ |
| | Connector, GASKET |
| | Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white |
| | 8156134 ⊵ |
| | Electrical component, Terminal box |
| | Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp |
| | 8156130 🗠 |
| | Connector, GASKET |
| | Gasket, 1" |
| | |
| | |

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

Product Detail | Reciprocating compressor, MT18JA3NVE

ENGINEERING TOMORROW



Accessories

| 1 | 1 |
|-----------|-----|
| 15 | 1 |
| Contra to | - |
| | - 1 |

8153010 🛛

Connector, Solder Sleeve Solder sleeve, P01 (1" rotolock, 3/8" ODF)



8153007 🛛

Connector, Solder Sleeve Solder sleeve, P06 (1" rotolock, 1/2" ODF)

Spare Parts



7754001 🗹 Lubricant, 160P

Mineral oil, 160P, 2-litre can



7754002 🖸

Lubricant, 160P Mineral oil, 160P, 5-litre can



7703004 🗠

Connector, Valve set Valve set, V06 (1"~1/2"), V01 (1"~3/8")



8156145 🖻 Connector, GASKET

Gasket for oil sight glass (black chloroprene)



7773106 🗠

Crankcase heater, Belt heater Belt type crankcase heater, 54 W, 230 V, CE mark, UL



120Z0459 🛛

Crankcase heater, PTC heater PTC heater 27W, CE mark, UL



8168031 🛛

Connector, Rotolock service valve Rotolock valve, V06 (1" rotolock, 1/2" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗷

Product Detail | Reciprocating compressor, MT18JA3NVE

ENGINEERING TOMORROW



Spare Parts



8168027 🖻

Connector, Rotolock service valve Rotolock valve, V01 (1" rotolock, 3/8" ODF)



8156019 🗹 Connector, Sight glass

Oil sight glass with gaskets (black and white)

For more information, please use this link to visit the product page on Danfoss Product Store 🗅