

# RESCUE® Motors Permanent Split Capacitor Condenser Fan 5.6" Diameter, Totally Enclosed, Air Over (TEAO)




## APPLICATIONS:

Commercial and Residential Condensing Units. Can replace a range of horsepower applications and a variety of mounting styles.

## FEATURES:

- High 158°F (70°C) Or 140°C (60°C) Ambient Designs
- Automatic Reset Thermal Overload Protector
- Suitable for Use With 370V Capacitors
- Special Treated Rotor For Corrosion Protection
- Includes Lead End Mounting Holes For Rheem®† or Trane®† Units
- 48" Leads
- Extended Mounting Studs
- Ball Bearings
- Reversible Rotation
- High Efficiency Design
- Continuous Duty, Air Over
- Discount Symbol DS-3HAC



**RESCUE® Condenser Motors  
available in 158°F (70°C)  
ambient ratings!**

HP	RPM	Voltage	Catalog Number	List	Max. Ambient	Speed Tap	Cap. MFD @ 208V	Cap. MFD @ 230V	Amps	Shaft N	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/3 1/4 1/5 1/6	825	208/230	5464	\$182	140°F (60°C)	High High Low Low	10 10 10 10	7.5 7.5 7.5 7.5	1.9 1.5 1.2 1.0	5	5.3	10.3	18	H43
1/3 1/4 1/5 1/6	825	208-230	5464H	\$186	158°C (70°C)	High High Low Low	10 10 10 10	7.5 7.5 7.5 7.5	1.9 1.5 1.2 1.0	5	5.3	10.3	18	H43
1/3 1/4 1/5 1/6	1075	208/230	5462	\$140	140°F (60°C)	High High Low Low	7.5 7.5 7.5 7.5	5 5 5 5	2.6 2.5 2.0 1.8	5	4.6	9.6	15	H43
1/3 1/4 1/5 1/6	1075	208-230	5462H	\$153	158°C (70°C)	High High Low Low	7.5 7.5 7.5 7.5	5 5 5 5	2.6 2.5 2.0 1.8	5	4.6	9.6	18.10	H43
1/2 1/3 1/4 1/5	1075	208-230	5465	\$177	140°F (60°C)	High High Low Low	12.5 12.5 12.5 12.5	10 10 10 10	3.0 2.2 1.6 1.3	5	5.3	10.3	19	H43
1/2 1/3 1/4 1/5	1075	208-230	5465H	\$190	158°C (70°C)	High High Low Low	12.5 12.5 12.5 12.5	10 10 10 10	3.0 2.2 1.6 1.3	5	5.3	10.6	14	H43
3/4 1/2 1/3 1/4	1075	208-230	5482H	\$205	158°C (70°C)	High High Low Low	15 15 15 15	15 15 15 15	4 2.8 1.9 1.4	5	6.3	11.9	14	H43

## 460 Volt RESCUE® Condenser Fan Motors

HP	RPM	Voltage	Catalog Number	List	Max. Ambient	Speed Tap	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Ship Wt. (lbs)	Notes
1/2 1/3 1/4 1/5 1/6	1075	460	5480H	\$240	158°C (70°C)	High High Low Low Low	10 10 10 10 10	1.3 0.9 0.7 0.5 0.5	5	5.6	11.1	19	H43
3/4 1/2 1/3 1/4	1075	460	5481H	\$260	158°C (70°C)	High High Low Low	15 15 15 15	2.2 1.3 1.1 0.7	5	6.3	11.9	22.38	H43

Note H43 Side Shell & Lead End Mounting Screws Included In Carton

† All marks shown within this document are properties of their respective owners.

