

Product Detail | Check valve, NRV 35s, Max. Working Pressure [bar]: 46.0

**020-1061** **Check valve, NRV 35s, Max. Working Pressure [bar]: 46.0**

Inlet connection type: Solder, ODF, Outlet connection type: Solder, ODF,

Direction: Angleway, Packing format: Multi pack

PRODUCT DETAILS

Gross weight	1.428 Kg
Net weight	1.306 Kg
Volume	3.328 Liter
EAN	5702422115236
Approval	C UL US LISTED CE EAC UKCA
Body material	Brass
China RoHS compliance	Out of scope
Connection material	Copper
Connection notes	Oversize
Cv value [gal/min]	33.52 gal/min
Design	Piston
Direction	Angleway
EU RoHS compliance	Out of scope
Flow direction	Single-flow
Flow direction indicator	Embossed 1-way arrow
Fluid Group	2
In scope of WEEE and contain batteries	No
Inlet connection type	Solder, ODF
Inlet size [in]	1 5/8 in
Kv value [m ³ /h]	29 m ³ /h
Lubricants compatibility	Oilfree applications
Max. Working Pressure [bar]	46 bar
Max. Working Pressure [psig]	667 psig
Min. Pressure drop [bar]	0.04 bar
Min. Pressure drop [psi]	0.6 psi
Oil free refrigerants	R1234ze(E) R134a R513A R515B
Outlet connection type	Solder, ODF
Outlet size [in]	1 5/8 in
Packing format	Multi pack
PED category	I
Product group	Check valves
Product Name Description	Check valve

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS

Quantity per packing format	6 pc
Rated cap cond, Hot gas [IMP]	tcond=86 °F tdisc=176 °F tevap=14 °F thotgas=140 °F tsub=9 °F
Rated cap cond, Hot gas [SI]	tcond=30 °C tdisc=80 °C tevap=-10 °C thotgas=60 °C tsub=5K
Rated cap cond, Liq. cap [IMP]	tcond=86 °F tevap=14 °F tsub=9 °F
Rated cap cond, Liq. cap [SI]	tcond=30 °C tevap=-10 °C tsub=5K
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerants	R1233zd(E) R1234yf R1234ze(E) R1270 R134a R170 R22/R407C R290 R32 R404A/R507A R407A R407F R407H R410A R448A R449A R449B R450A R452A R452B R454A R454B R454C R455A R513A R515B R516A R600 R600a
SCIP dossier no.	b3a34751-5701-488e-98f4-24be945efdc1
Temperature range [°C] [max]	140 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	285 °F
Temperature range [°F] [min]	-58 °F
Type	NRV 35s
UK RoHS compliance	Out of scope

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

UL approval file name	REFRIGERANT VALVE 53R0
UL approved refrigerants	R1233zd(E) R1234yf R1234ze(E) R1270 R134a R170 R22 R290 R32 R404A R407A R407C R407F R407H R410A R448A R449A R449B R450A R452A R452B R454A R454B R454C R455A R507A R513A R515B R516A R600 R600a

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)