

**014L0025****SGP 12 I, Sight glass, Flare, 12.00 mm, Flare, 12.00 mm**

Inlet connection type: Flare, Inlet size [mm]: 12.00, Outlet connection type:

Flare, Outlet size [mm]: 12.00

PRODUCT DETAILS

| | |
|--|---|
| Gross weight | 0.228 Kg |
| Net weight | 0.201 Kg |
| Volume | 0.141 Liter |
| EAN | 5702428838535 |
| Approval | C UL US LISTED EAC |
| Approval file name | REF. LIQUID INDICATOR 76H4 |
| Body material | Brass |
| China RoHS compliance | Yes exceed limitations |
| Connection material | Brass |
| EU RoHS compliance | Yes with exemptions |
| EU RoHS exemption clause | 6(c) |
| Green: max moist con@25 °C | R22: 150 ppm |
| Green: max moist con@43 °C | R22: 250 ppm |
| Identical product | 014L0075 |
| In scope of WEEE and contain batteries | No |
| Inlet connection type | Flare |
| Inlet Internal/External | Internal |
| Inlet size [in] | 1/2 in |
| Inlet size [mm] | 12 mm |
| Max. Working Pressure [bar] | 52 bar |
| Max. Working Pressure [psig] | 754 psig |
| Moisture indicator | I indicator |
| Outlet connection type | Flare |
| Outlet Internal/External | External |
| Outlet size [in] | 1/2 in |
| Outlet size [mm] | 12 mm |
| Packing format | Multi pack |
| Product accessories | Generic accessories |
| Product group | Sight glasses |
| Product Name Description | Sight glass |
| Quantity per packing format | 24 pc |
| REACH Candidate List substances | Lead (CAS no. 7439-92-1) Cobalt dichloride (CAS no. 7646-79-9) |
| Refrigerants | R22 |
| SCIP dossier no. | 323c7b85-ff73-43cd-8fce-a44eabbf5297 |
| Serviceable | No |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | SGP 12 I, Sight glass, Flare, 12.00 mm, Flare, 12.00 mm**PRODUCT DETAILS**

| | |
|-------------------------------------|----------------------------|
| Temperature range [°C] [max] | 80 °C |
| Temperature range [°C] [min] | -50 °C |
| Temperature range [°F] [max] | 175 °F |
| Temperature range [°F] [min] | -58 °F |
| Type | SGP 12 I |
| UK RoHS compliance | Out of scope |
| UL approval file name | REF. LIQUID INDICATOR 76H4 |
| UL approved refrigerants | R22 |
| Yellow: min moist con@25 °C | R22: 300 ppm |
| Yellow: min moist con@43 °C | R22: 500 ppm |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)