

**023U1392** **Filter drier, core, DCR, 48-DM**

Product Type: DM, Gasket included: Yes

**PRODUCT DETAILS**

<b>Gross weight</b>	0.686 Kilogram
<b>Net weight</b>	0.565 Kilogram
<b>Volume</b>	2.111 Liter
<b>EAN</b>	5702428004817
<b>Acid capacity [g]</b>	3.56 g
<b>Acid capacity [oz]</b>	0.126 oz
<b>Activated alumina [%]</b>	0 %
<b>Brand</b>	ELIMINATOR
<b>Core Size code</b>	48 cu.in.
<b>Core type</b>	Solid core
<b>Drying Cap[Drops of Water]24°C</b>	R1234ze: 1766 R134a: 1652 R404A: 1721 R407C: 1605 R410A: 1496 R452A: 1707 R507: 1803
<b>Drying Cap[Drops of Water]52°C</b>	R1234ze: 1588 R134a: 1513 R404A: 1630 R407C: 1479 R410A: 1331 R452A: 1590 R507: 1622
<b>Filter application</b>	High Moisture Capacity
<b>Gasket included</b>	Yes
<b>In scope of WEEE and contain batteries</b>	No
<b>Lubricants compatibility</b>	Oilfree applications
<b>Molecular sieve [%]</b>	100 %
<b>Oil free refrigerants</b>	R1234ze(E) R134a R513A R515A R516A
<b>Packing format</b>	Industrial pack
<b>Parts included</b>	1 x Gasket (023U0743) 2 x Felt gasket (633L5312)
<b>Parts Program name</b>	DCR
<b>Product group</b>	Filter driers

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Filter drier, core, DCR, 48-DM

## PRODUCT DETAILS

Product Name Description	Filter drier, core
Quantity per packing format	8 pc
REACH Candidate List substances	No
Refrigerants	R134a R22/R407C R290 R401A R402A R404A R409A R410A R421A R422D R502 R507A R744
Solid core surface [cm2]	612 cm <sup>2</sup>
Solid core surface [in2]	95 in <sup>2</sup>
Solid core volume [cm3]	727 cm <sup>3</sup>
Solid core volume [in3]	44 in <sup>3</sup>
Type	DM
Type designation	48-DM

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)