

Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Name: Armaflex WB Finish.
Description: Water Based Paint.

II. DEPARTMENT OF TRANSPORTATION INFORMATION

Shipping name: Paint, water Based, Not Hazardous, Not Regulated
Hazard Class: None. ID # N/A.
EMERGENCY ONLY CONTACT: CHEM-TEL 800-255-3924

III. HMIS (0 = minimal hazard; 4 = severe hazard)

Toxicity = 1 Fire = 0 Reactivity = 0

IV. PRODUCT CONTENT

This product **does not contain** chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR Part 372. All components are on TSCA Inventory. This product does NOT contain asbestos or polychlorinated biphenyls.

V. HAZARDOUS INGREDIENTS

<u>(Chemical Identity: Common Name)</u>	<u>C.A.S. No.</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TVL</u>
Butyl Benzyl Phthalate	85-68-7	<9	N/A	N/A

VI. PHYSICAL DATA

APPEARANCE AND COLOR: White latex paint — Mild Odor .
BOILING POINT (°F):212. VAPOR PRESSURE (mm Hg @ 20°C): 17.
VAPOR DENSITY (Air = 1); Greater than air. . SOLUBILITY IN
WATER: Dilutable when wet SPECIFIC GRAVITY (H₂O=1) 1.41.
PERCENT VOLATILE BY VOLUME (30 min.@275°F): 56.5:
EVAPORATION RATE (Butyl Acetate=1) :Slow, water. VOC: <5 g/l

VII. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: none. FLAMMABLE RANGE: LEL = N/K; UEL = N/K
EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, Water Spray.
Foam SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from
toxic products of combustion by wearing self-contained breathing
apparatus. UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers
in a fire may rupture due to pressure build-up; use water to cool
containers to prevent this.

VIII. HEALTH HAZARD DATA

PRIMARY ROUTE (S) OF ENTRY: Inhalation and direct dermal exposure.
TARGET ORGANS: Lung, skin and eyes. EFFECTS OF OVEREXPOSURE:
SKIN AND EYES: Excessive skin contact may cause irritation. Contact
with eyes may cause irritation. INHALATION: May cause irritation of
respiratory tract, and CNS effects such as headache, dizziness,
drowsiness, nausea. Chronic overexposure to spray mist or sanding
dust may cause dust disease of the lungs. CARCINOGENICITY: NTP: No
IARC Monographs: No. OSHA Regulated: No. MEDICAL CONDITIONS
GENERALLY AGGRAVATED BY EXPOSURE: N/K. FIRST AID PROCEDURES:
SKIN AND EYES: Flush any skin or eye contact with plenty of water.
Refer to physician if irritation or symptoms persist. INHALATION:
Remove to fresh air if exposed to excess concentrations of vapor.
Seek medical attention if symptoms persist.

IX. REACTIVITY DATA

STABILITY: Stable. INCOMPATIBILITY: none known. HAZARDOUS
DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and
other toxic vapors and gases that are common to thermal degradation
of organic compounds. HAZARDOUS POLYMERIZATION: Will not occur.

X. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Ventilate area
of spill or leak For exposures above TLV, wear approved respiratory
equipment. Contain spill, preventing it from entering sewer lines or
waterways. Use absorbent to assist with the pick-up of material.
WASTE DISPOSAL METHOD: Dispose of container and any unused

Armaflex WB Finish

Prepared 1/11 –Replaces 7/07

Armacell LLC
7600 Oakwood Street Extension
Mebane, NC 27302
(919) 304-3846

contents in accordance with Federal, State and Local Waste Disposal
Regulations. Do not flush unused contents or residue down drains.

XI. SPECIAL HANDLING AND USE INFORMATION

VENTILATION: Use only with adequate ventilation. Provide general or
local exhaust ventilation in volume and pattern to keep air
contaminant concentration below current applicable safety and health
standards in the mixing, application and curing areas, and to remove
sanding dust of dry coating. RESPIRATORY PROTECTION: Do not
breathe vapors, spray mist or sanding dust. When applied in outdoor
or open areas with unrestricted ventilation, and during sanding or
grinding operations, use NIOSH approved mechanical filter respirator
to remove solid airborne particles of overspray and sanding dust.
When used in restricted ventilation areas, wear NIOSH approved
chemical/mechanical filters designed to remove a combination of
particles and vapor. Follow respirator manufacturer's directions for
respirator use. SKIN AND EYE PROTECTION Do not get into eyes.
During normal end product use spectacle-type safety glasses are
recommended to prevent contact.

XII. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store below
110°F and keep from freezing. Keep container closed when not in
use. Do not reuse empty containers.. OTHER PRECAUTIONS: None.

The information presented herein is supplied as a guide to those who
handle or use this product. Safe work practices must be employed
when working with any materials. It is important that the end user
makes a determination regarding the adequacy of the safety
procedures employed during the use of this product.

N/A -not applicable or not available
N/K – none known or not known