



Backing: Foil/Scrim/Kraft Paper Laminate Backing Adhesive Adhesive: Synthetic Rubber Liner Liner: Unbleached Natural Kraft Paper Colors: Aluminum Specifications: Tested in accordance with UL723 Standard Sizes: 72mm x 46M Applications

• Vapor barrier seal for insulation facing

• Sealing insulation and repairing in cooler/ refrigeration applications

Features	Benefits
Foil/Scrim/Kraft Laminate Backing	High strength and tear resistant
	 UV, moisture, and mold resistant
Synthetic Rubber Adhesive	 Non-solvent for less odor and low VOC content
	 Super high tack, aggressive bond to surfaces
Low VOC Content	Can contribute toward satisfying EQ Credit 4.1
	(Low Emitting Materials) under LEED®

Typical Test Values				
	Standard UOM	Metric UOM	Test Method	
Total Thickness	9.25 mils	0.235 mm	ASTM D-1000	
Adhesion to Steel	70 oz/in	7.66 N/cm	PSTC-101	
Tensile Strength	35 lb/in	61.29 N/cm	ASTM D-1000	
Operating Temperature	40 to 200 °F	4 to 93 °C		
WVTR	>0.02 Perms		Mocon (100° F, 90% RH)	
Smoke Developed	15			
Flame Spread	15			
VOC Content	<1 g/L			

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.