

**MTZ56-3VI****Reciprocating compressor, MTZ56HL3BVE**

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R454A; R455A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	40.5 Kg
Net weight	38 Kg
Volume	61.54 Liter
EAN	5702428887984
Approval	CCC CE UL UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	MTZ056-3
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502012g
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ56HL3BVE

PRODUCT DETAILS

High Side Volume	0.6 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 60Hz [V]	200 V
Low value of voltage range at 60Hz [V]	180 V
LRA	130 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	22.6 bar
MCC	24 A
Model number	MTZ56HL3BVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	39 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor MTZ
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R134a R404A R407A R407C R407F R448A R449A R452A R513A R454A R454C R455A
Rotational speed at 60Hz [rpm]	3500 rpm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ56HL3BVE
PRODUCT DETAILS

SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1 3/4 in
Swept volume [cm³]	96.13 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	413 mm
Type	MTZ056
UK RoHS compliance	Out of scope
Winding resistance for three- phase compressors with identical windings [Ohm]	0.56 Ohm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories

120Z0763 [🔗](#)
Mounting, Compressor kit

Mounting kit 2 cylinder


8156132 [🔗](#)
Connector, Gasket

Gasket, 1-3/4"


120Z0576 [🔗](#)
Acoustic hood, Reciprocating

Acoustic hood for two-cylinder compressor


8153008 [🔗](#)
Connector, Solder sleeve

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories



8156009 [🔗](#)

Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



7750009 [🔗](#)

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8156134 [🔗](#)

Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp



8153013 [🔗](#)

Connector, Solder sleeve

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)



8156131 [🔗](#)

Connector, Gasket

Gasket, 1-1/4"

Spare Parts



7773107 [🔗](#)

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 230 V



8156019 [🔗](#)

Connector, Sight glass

Oil sight glass with gaskets (black and white)



8168032 [🔗](#)

Connector, Rotolock service valve

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)



120Z0459 [🔗](#)

Crankcase heater, PTC heater

PTC heater 27W

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ56HL3BVE

Spare Parts

**120Z0638** [🔗](#)**Lubricant, 175PZ**

POE lubricant, 175PZ, 1-litre can

**120Z0639** [🔗](#)**Lubricant, 175PZ**

POE lubricant, 175PZ, 2.5L CAN

**7773109** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 110 V

**8156145** [🔗](#)**Connector, Gasket**

Gasket for oil sight glass (black chloroprene)

**7703006** [🔗](#)**Connector, Valve set**

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")

**8168029** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.