

**123B1311** [↗](#)**Reciprocating compressor, GPY14NDa**

Refrigerants: R134a, Segment usage: Refrigeration LT; Refrigeration MT,  
Compressor power supply [V]: 115/1/60

**PRODUCT DETAILS**

<b>Gross weight</b>	12.5 Kg
<b>Net weight</b>	12.2 Kg
<b>Volume</b>	13.1 Liter
<b>EAN</b>	5702428584630
<b>Applications</b>	LBP MBP
<b>Auxiliary winding resistance (start winding) for single-phase compressors [Ohm]</b>	7.89
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Black
<b>Compressor power supply [V]</b>	115/1/60
<b>Configuration code</b>	Single
<b>Cut in current HST 60Hz [A]</b>	39 A
<b>Description</b>	GPY14NDa
<b>Discharge connection angle [°]</b>	0 °
<b>Discharge connection comments</b>	Rubber plug
<b>Discharge connection diameter [mm]</b>	6.5 mm
<b>Discharge connection height [mm]</b>	121 mm
<b>Discharge connection material</b>	Copper
<b>Economizer</b>	No
<b>Family</b>	P
<b>Frequency [Hz]</b>	60
<b>Height from baseplate [mm]</b>	211 mm
<b>High value of nominal voltage at 60Hz [V]</b>	115 V
<b>High value of voltage range at 60Hz [V]</b>	132 V
<b>In scope of WEEE and contain batteries</b>	No
<b>Low value of nominal voltage at 60Hz [V]</b>	115 V
<b>Low value of voltage range at 60Hz [V]</b>	98 V
<b>LRA HST 60Hz [A]</b>	39 A
<b>Main winding resistance for single-phase compressors [Ohm]</b>	1.02

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | Reciprocating compressor, GPY14NDa

## PRODUCT DETAILS

MCC	8.00 A
Model number	GPY14NDa
Motor type	CSIR
No. of phases (compressor)	1
Oil quantity [cm <sup>3</sup> ]	400 cm <sup>3</sup>
Oil type	POE
Packing format	Single pack
Packing quantity	1
Process connection angle [°]	50 °
Process connection comments	Rubber plug
Process connection diameter [mm]	8.1 mm
Process connection material	Copper
Product group	Hermetic compressors
Product Name Description	Reciprocating compressor P
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	1.15 kg
Refrigerants	R134a
Rotational speed at 60Hz [rpm]	3600 rpm
SCIP dossier no.	cd1d92df-acc4-43d9-8eb6- bb380e61d93f
SCIP dossier product name	GL
Segment usage	Refrigeration LT Refrigeration MT
Start capacitor capacitance	125 µF
Suction connection angle [°]	20 °
Suction connection diameter [mm]	8.1 mm
Suction connection height [mm]	125 mm
Suction connection material	Copper
Swept volume [cm <sup>3</sup> ]	14.32 cm <sup>3</sup>
Technology	Reciprocating
Total height [mm]	217 mm
Type	GPY14
Voltage 60Hz [V]	115 V
Voltage 60Hz [V] [Max]	115 V
Winding temperature short term [°F] [Max]	135 °C
Winding temperature stat [°C] [Max]	115 °C
Proposition 65	WARNING: Cancer and Reproductive Harm <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

---

**Accessories**

---

**123B9138** [🔗](#)**Electrical component, Relay**

Relay + Con. Board ECC2 1191-8

**123B9707** [🔗](#)**Electrical component, Terminal box cover**

Plastic Cover, UL

**123B9901** [🔗](#)**Mounting, Mounting kit**

Mounting Accessories 16mm

---

**Spare Parts**

---

**123B9320** [🔗](#)**Electrical component, Start capacitor**

Starting Cap. 125µf/160V +Cover+Cable

**123B9494** [🔗](#)**Electrical component, Motor protector**

Protector 9-551

**123B9701** [🔗](#)**Electrical component, Cable**

Cord Anchorage

---

**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.