

**114N2024****OP-UCGC0050UWC000B**

Segment usage: Low Back Pressure; Universal; Medium Back Pressure,  
Refrigerants: R134a, Compressor power supply [V]: 115/1/60

**PRODUCT DETAILS**

Gross weight	28.95 Kg
Net weight	27 Kg
EAN	5702428391481
Air flow @ 60Hz [m <sup>3</sup> /h]	830 m <sup>3</sup> /h
Applications	HBP
	LBP
	MBP
Approval	UL listed
Approval file name	52L3
Compressor model	SC18G
Compressor power supply [V]	115/1/60
Condenser type	BM72
Description	OP-UCGC0050UWC000B
Electrical code	B
Family	Optyma™
Fan blade size [mm]	254 mm
Fan current @ 60Hz [A]	1 A
Fan power consumption @ 60Hz [W]	60 W
Fan power output @ 60Hz [W]	16 W
Fan power supply [V/Ph/Hz]	115/1/60
Fan voltage @ 60Hz (max) [V] [Max]	115 V
Fan voltage @ 60Hz (max) [V] [Min]	115 V
Frequency [Hz]	60 Hz
High value of nominal voltage at 60Hz [V]	115 V
In scope of WEEE and contain batteries	No
Length [mm]	432 mm
Liquid line connection [in]	1/4 in
Low value of nominal voltage at 60Hz [V]	115 V
Model number	OP-UCGC0050UWC000B
No. of phases (compressor)	1
No. of phases (fan)	1
Number of fans	1
Phase	1
Phases of Compressor	1
Phases of Fan	1
Product group	Condensing Units

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

## Product Detail | OP-UCGC0050UWC000B

## PRODUCT DETAILS

Product Name Description	Bare unit
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Receiver approval	UL
Receiver volume [L]	0.8 L
Refrigerants	R134a
Region	North America
RLA	10 A
Segment usage	Low Back Pressure Medium Back Pressure Universal
Suction connection size [in]	3/8 in
Technology	Reciprocating
Total height [mm]	300 mm
Type	Optyma™ WC
Version	WC
Voltage 60Hz [V]	115 V
Voltage 60Hz [V] [Max]	115 V
Width [mm]	330 mm
Proposition 65	WARNING: Cancer and Reproductive Harm <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

## Accessories

**117U5028** [🔗](#)**Electrical component, Start capacitor**

START CAPACITOR 410µF, 125V - NF

## Spare Parts

**119-2276** [🔗](#)**Condensing Units Accessories & Spare parts, Compressor**

SC18G

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.