

**060L5208****Thermostat, KPU73**

This product is not available in this store. Please contact your local [Customer Service Center](#).

Customer Service Center

Thermostat, Product Type: KPU73, Reset function: Auto, Contact function: SPDT, Sensor type: Remote bulb, Temperature range [°C] [min]: -26, Temperature range [°C] [max]: 15

PRODUCT DETAILS

Gross weight	0.785 Kilogram
Net weight	0.746 Kilogram
Volume	1.595 Liter
EAN	5702428075626
Amb. Temp. Note	80 °C/176 °F for max 120 min
Ambient temperature range [°C] [max]	50 °C
Ambient temperature range [°C] [min]	-40 °C
Ambient temperature range [°F] [max]	122 °F
Ambient temperature range [°F] [min]	-40 °F
Approval	CE LVD RoHS UKCA c UL us UL873, CS C22.2
Cap. tube length fraction [in]	80 in
Capillary tube length [mm]	2030 mm
Charge type	Adsorption
China RoHS compliance	Out of scope
Contact function	SPDT
Contact rating	120/240 V ac, 24 FLA, 144 LRA Pilot Duty: 120/240 V dc 12W
Diff. @ Max. range setting[°F] [max]	50 °F
Diff. @ Max. range setting[°F] [min]	5 °F
Diff. @ Min. range setting[°F] [max]	32 °F
Diff. @ Min. range setting[°F] [min]	6.5 °F
Differential type	Adjustable
Electrical conn. comments	for ½ in male pipe thread
Electrical connection	Hole
Electrical connection size	7/8 in
Electrical spec. standard	EN 60947-4/-5
EN 60947 electrical properties	Insulation: 400V Pollution degree: 3 Rated impulse voltage: 4 kV Short circuit prot, fuse: 16A
EN 60947 wiring properties	Flex, ferrules: 0.5-1.5 mm2

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Thermostat, KPU73

PRODUCT DETAILS

	Flex, no ferrules: 0.7-2.5 mm ² Solid/stranded: 0.75-2.5 mm ²
Enclosure rating IP	IP30
Enclosure rating Nema (~)	1
EU RoHS compliance	Yes
EU RoHS exemption clause	No
In scope of WEEE and contain batteries	No
Max. sensor temperature [°C]	80 °C
Max. sensor temperature [°F]	175 °F
Packing format	Multi pack
Parts included	Angle bracket Screws
Product accessories	Switches accessories
Product description	Temperature Control
Product group	Switches and thermostats
Product Name Description	Thermostat
Quantity per packing format	14 pc
REACH Candidate List substances	No
Reset function	Auto
Sensor size (Ø x L) [in]	3/8 x 3 3/8 in
Sensor size (Ø x L) [mm]	9.5 x 85 mm
Sensor type	Remote bulb
Serviceable	No
Temperature range [°C] [max]	15 °C
Temperature range [°C] [min]	-26 °C
Temperature range [°F] [max]	60 °F
Temperature range [°F] [min]	-15 °F
Type	KPU73
UK RoHS compliance	Out of scope
UL approval file name	E31024

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories



017-420166 [🔗](#)

Switches accessories, Sensor Holder Kit

Sensor Holder Kit, Packing format: Multi pack, Quantity per packing format: 20



017-420366 [🔗](#)


Switches accessories, Sensor Clamp

Sensor Clamp, Packing format: Multi pack, Quantity per packing format: 20

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**017-420466** [🔗](#)**Switches accessories, Clamping Band Ass'y**

Clamping Band Ass'y, Packing format: Multi pack, Quantity per packing format: 10

**017-421666** [🔗](#)**Switches accessories, Sensor Pocket**

Sensor Pocket, Packing format: Multi pack, Quantity per packing format: 12

**017-422066** [🔗](#)**Generic accessories, Tube Gland For RT**

Tube Gland For RT, Packing format: Multi pack, Quantity per packing format: 5

**017-436966** [🔗](#)**Switches accessories, Sensor Pocket KP/RT Stainless 112mm G 1/2"**

Sensor Pocket KP/RT Stainless 112mm G 1/2", Packing format: Multi pack, Quantity per packing format: 10

**017-437066** [🔗](#)**Switches accessories, Sensor Pocket KP/RT 112mm G 1/2"**

Sensor Pocket KP/RT 112mm G 1/2", Packing format: Multi pack, Quantity per packing format: 10

**060L327366** [🔗](#)**Switches accessories, Gasket Set For Sensor Pocket**

Gasket Set For Sensor Pocket, Packing format: Multi pack, Quantity per packing format: 10

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.