



121L1293 🕑

Scroll compressor, HRH051U1LP6

Refrigerants: R410A, Segment usage: Air conditioning, Compressor power supply [V]: 208-230/1/60, Packing format: Industrial pack

PRODUCT DETAILS

PRODUCT DETAILS	
Gross weight	43 Kilogram
Net weight	41 Kilogram
Volume	0.06 Cubic meter
EAN	5702424234416
Approval	CE
	UL
	UKCA
Auxiliary winding resistance	0.82
(start winding) for single-phase	
compressors [Ohm]	
Brand technique	Scroll compressor
Capacity control	Fixed speed
Capacity of capacitor A	70 µF
Capacity of capacitor B	161-193 μF
CE evaluated	Yes
China RoHS compliance	Yes exceed limitations
Colour	Blue
Compressor power supply [V]	208-230/1/60
Configuration code	Single
Connection type	Brazed
Description	HRH051U1
Diameter [mm]	184 mm
Discharge connection height [mm]	422 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1/2 in
Drawing number	0XR6002B-2
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	7(c)-I
	6(a)
	6(a)-I
	6(c)
	7(a)
	8(b)
Family	HRH
Fitting standard	ODF
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	None

Product Detail | Scroll compressor, HRH051U1LP6





PRODUCT DETAILS

Gaz equalization	None
Glass mounting	None
High value of nominal voltage at	230 V
60Hz [V]	
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP22
Length [mm]	239 mm
Low value of nominal voltage at	208 V
60Hz [V]	
Low value of voltage range at 60Hz	187 V
[V]	
LRA	150 A
Main winding resistance for single-	0.32
phase compressors [Ohm]	
Max pressure (PS) - high side	46.1 bar
Max pressure (PS) - low side	31.1 bar
мсс	41 A
Model number	HRH051U1LP6
Motor protection	Internal overload protector
Network power supply [V/Ph/Hz]	208-230/1/60
Oil charge [L]	1.57 L
Oil drain	None
Oil equalization	None
Oil reference	320HV
Oil type	PVE
Packing format	Industrial pack
Packing quantity	12
Phase	1
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	Scroll compressor HRH
Refrigerant charge [kg] [Max]	5.44 kg
Refrigerants	R410A
Relay model	3ARR3*3L*
RLA	26.3 A
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Air conditioning
Suction connection height [mm]	280 mm
Suction connection material	<u>-</u>
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	7/8 in
Swept volume [cm3]	49.32 cm ³
Technology	Scroll
Total height [mm]	455 mm
Type	HRH051
U.S. EPA label	For installations using U.S. EPA
	restricted refrigerants, this product
	may be used for servicing
	existing equipment only.



PRODUCT DETAILS

19 21
21
21
24
12
13
18
Yes
68 cP
370 V
250 V
239 mm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories	
	120Z0400 ⊵ Electrical component, Start capacitor Capacitor 161-193μF 330V
	120Z5084 № Acoustic hood, Scroll Acoustic hood
	8156130 ☑ Connector, Gasket Gasket, 1"
	8156009 🗹 Connector, Gasket Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white
0	7750009 🖻 Electrical component, Discharge thermostat kit Discharge thermostat kit
	120Z5064 🗷 Mounting, Compressor kit Mounting kit for one-scroll compressor, including 4 grommets, 4 sleeves, 4 bolts, 4 washers

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Product Detail | Scroll compressor, HRH051U1LP6

ENGINEERING TOMORROW



0	8153007 🛛 Connector, Solder sleeve Solder sleeve, P06 (1" rotolock, 1/2" ODF)
	120Z0127 ☑ Connector, Solder sleeve adapter set Solder sleeve adaptor set (1-1/4" rotolock, 7/8" ODF), (1" rotolock, 1/2" ODF)
S	8168030 ☑ Connector, Rotolock service valve Rotolock valve, V05 (1-1/4" rotolock, 7/8" ODF)
	118U0056 ☑ Electrical component, IP Upgrade kit IP54 upgrade kit
	8168031 ☑ Connector, Rotolock service valve Rotolock valve, V06 (1" rotolock, 1/2" ODF)
	120Z0051 ⊵ Electrical component, Run capacitor Run capacitor 70 μF
	8156131 ₪ Connector, Gasket Gasket, 1-1/4"
<u>)</u>	120Z0057 ট Crankcase heater, Belt heater Belt type crankcase heater, 50 W, 230 V

Spare Parts



Crankcase heater, Belt heater Belt type crankcase heater, 50 W, 230 V

For more information, please use this link to visit the product page on Danfoss Product Store 🗈



Ŭ	120Z5034 ⊠ Lubricant, 320HV PVE lubricant, 320HV (FVC68D), 1-litre can	
1 and 1	8168030 대 Connector, Rotolock service valve Rotolock valve, V05 (1-1/4" rotolock, 7/8" ODF)	
	120Z5015 Electrical component, Terminal box Terminal box	
-	8168031 ☑ Connector, Rotolock service valve Rotolock valve, V06 (1" rotolock, 1/2" ODF)	

For more information, please use this link to visit the product page on Danfoss Product Store 🗈