

**068N7680****Thermostatic expansion valve, TD 1, R404A**

Temperature range [°C]: -40 - 10, Orifice capacities [kW]: 1.13, Orifice capacities [TR]: 0.32, Pressure equalization: Internally equalized

PRODUCT DETAILS

Gross weight	0.227 Kilogram
Net weight	0.204 Kilogram
Volume	0.489 Liter
EAN	5702424615246
Type	TD 1
Product group	Expansion valves
Product Name Description	Thermostatic expansion valve
Adjustable	Yes
Approval	C UL US LISTED
Balanced port [Yes/No]	No
Body material	Brass
Capillary tube length [in]	30 in
Capillary tube length [mm]	750 mm
China RoHS compliance	Yes with exemptions
Connection material	Copper
Contain batteries	No
Direction	Straightway
Element temperature max. [°C]	100 °C
Element temperature max. [°F]	210 °F
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Factory setting [bar]	5.3 bar
Factory setting [psig]	76.9 psig
Filter	Integrated
Flow direction	Single-flow
Flow direction indicator	Stamped 1-way arrow
Inlet connection type	Solder, ODF
Inlet size [in]	3/8 in
Max. Working Pressure [bar]	34 bar
Max. Working Pressure [psig]	500 psig
Orifice capacities [kW]	1.13 kW
Orifice capacities [TR]	0.32 TR
Orifice size	1
Outlet connection type	Solder, ODF
Outlet size [in]	1/2 in
Packing format	Multi pack
Parts included	Bulb strap
Pressure equalization	Internally equalized

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Product accessories	TXV accessories
Quantity per packing format	20 pc
Rated cap. cond. Range N [IMP]	tcond=90 °F tevap=41 °F tliq=82 °F
Rated cap. cond. Range N [SI]	tcond=32 °C tevap=5 °C tliq=28 °C
Refrigerants	R404A
Serviceable	No
Static Superheat (SS) [°C]	3 °C
Static Superheat (SS) [°F]	5.4 °F
Superheat setting	Adjustable
Temperature range [°C] [max]	10 °C
Temperature range [°C] [min]	-40 °C
Temperature range [°F] [max]	50 °F
Temperature range [°F] [min]	-40 °F
UL approval file name	SA7200
UL evaluated	Yes

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)