

067L6008**Thermostatic expansion valve, TR 6, R410A; R32; R454B**

This product is not available in this store. Please contact your local [Customer Service Center](#).

[Customer Service Center](#)

Temperature range [°C]: -10 - 15, MOP Point [psig]: LAH, Orifice size: 5,
Orifice capacities [kW]: 19.7, Orifice capacities [TR]: 5.6

Image coming soon

PRODUCT DETAILS

Gross weight	0.606 Kilogram
Net weight	0.557 Kilogram
Volume	1.721 Liter
EAN	5715255105831
Type	TR 6
Product group	Expansion valves
Product Name Description	Thermostatic expansion valve
Adjustable	Yes
Approval	c UL us
Body material	Brass
Capillary tube length [in]	31.5 in
Capillary tube length [mm]	800 mm
Check valve	Yes
Direction	Straightway
Equal. Capillar tube lgt. [in]	24.3 in
Equalization connection type	Cap. tube, flare
Equalization size [in]	1/4 in
Factory setting [bar]	9.35 bar
Inlet connection type	Solder, ODF
Inlet fitting variant	067U0087
Inlet size [in]	3/8 in
Max. Working Pressure [bar]	49 bar
Max. Working Pressure [psig]	711 psig
MOP Point [psig]	LAH
Orifice capacities [kW]	19.7 kW
Orifice capacities [TR]	5.6 TR
Orifice size	5
Outlet connection type	Solder, ODF
Outlet fitting variant	067U0087
Outlet size [in]	3/8 in
Packing format	Multi pack
Port design	Balance port
Quantity per packing format	12 pc
Rated capacity R32 [kW]	28.1 kW
Rated capacity R32 [TR]	8 TR
Rated capacity R410A [kW]	17.6 kW
Rated capacity R410A [TR]	5 TR
Refrigerants	R32

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Thermostatic expansion valve, TR 6, R410A; R32; R454B**PRODUCT DETAILS**

	R454B
	R410A
Static Superheat (SS) [°C]	3.01 °C
Static Superheat (SS) [°F]	5.41 °F
Temperature range [°C] [max]	15 °C
Temperature range [°C] [min]	-10 °C
Temperature range [°F] [max]	60 °F
Temperature range [°F] [min]	15 °F

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)