



All Service Jacketing (ASJ) Insulation Tape

Backing Adhesive Release	Backing:	ASJ Kraft/Scrim/Foil Laminate	
	Adhesive:	Acrylic	
	Liner:	Polycoated Natural Kraft Paper	
	Colors:	White	
	Specifications	: Tested in accordance with UL 723	
	Standard Size	s: 72mm x 46M	
	Applicat	ions	

Vapor barrier seal for ASJ-faced duct board, pipe insulation, and thermal jacketing

 Sealing insulation and repairing in cooler/ refrigeration applications

Features	Benefits
White Kraft/Scrim/Foil Laminate Backing	High strength and tear resistant
	Mold resistant
Acrylic Adhesive	Low odor adhesive
	 Super high tack, aggressive bond to surfaces
Low VOC Content	 Can contribute toward satisfying EQ Credit 4.1
	(Low Emitting Materials) under LEED®

Typical	Test Values	
rypicui	i cst values	

Typical rest values							
	Standard UOM	Metric UOM	Test Method				
Total Thickness	11.0 mils	0.279 mm	ASTM D-1000				
Adhesion to Steel	50 oz/in	5.47 N/cm	PSTC-101				
Tensile Strength	45 lb/in	78.81 N/cm	ASTM D-1000				
Operating Temperature	-35 to 260 °F	-37 to 126 °C					
Smoke Developed	25						
Flame Spread	5						
WVTR	0.02 perms		ASTM E96				
Emmissivity	0.03		ASTM E408				
VOC Content	<1 g/L						

Recommended Storage Conditions: 40-60% Humidity, 60 °F - 80 °F

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.