

Product Detail | Reciprocating compressor, MT56HL1EVE

**MT56-1VI****Reciprocating compressor, MT56HL1EVE**

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply

[V]: 208-230/1/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	40.5 Kg
Net weight	38 Kg
Volume	61.54 Liter
EAN	5702428839617
Approval	CE UL UKCA
Auxiliary winding resistance (start winding) for single-phase compressors [Ohm]	1.64
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Capacity of capacitor A	35 µF
Capacity of capacitor B	200 µF
Capacity of capacitor C	20 µF
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	208-230/1/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	MT056-1
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502011e
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MT
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT56HL1EVE

PRODUCT DETAILS

Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	0.6 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP54 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at 60Hz [V]	208 V
Low value of voltage range at 60Hz [V]	187 V
LRA	136 A
Main winding resistance for single-phase compressors [Ohm]	0.33
Max pressure (PS) - high side	27.8 bar
Max pressure (PS) - low side	18.4 bar
MCC	42.5 A
Model number	MT56HL1EVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/1/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	39 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	1
Power connections	Screw connectors 10-32 UNF x 9.5
Product group	Hermetic compressors
Product Name Description	MT
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	5 kg
Refrigerants	R22
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b
Segment usage	Refrigeration MT

Product Detail | Reciprocating compressor, MT56HL1EVE

PRODUCT DETAILS

Shipped fittings	Suction and discharge solder sleeves, rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1 3/4 in
Swept volume [cm ³]	96.13 cm ³
Technology	Reciprocating
Test Dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	413 mm
Type	MT056
UK RoHS compliance	Out of scope
Viscosity [cP]	32 cP
Voltage of capacitor A [V]	440 V
Voltage of capacitor B [V]	330 V
Voltage of capacitor C [V]	440 V
Proposition 65	WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories



8156135 [🔗](#)

Electrical component, Terminal box

Service kit for terminal box 96 x 115 mm, including 1 cover, 1 clamp



7701026 [🔗](#)

Electrical component, Starting kit

PSC starting kit, 20 µF, 10 µF



8173230 [🔗](#)

Electrical component, T block

T block connector 52 x 57 mm

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT56HL1EVE

Accessories

**8156131** **Connector, GASKET**

Gasket, 1-1/4"

**8153008** **Connector, Solder Sleeve**

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)

**8156009** **Connector, GASKET**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

**8173001** **Electrical component, Start capacitor**

Start capacitor 330V, 98 µF

**7701156** **Electrical component, Starting kit**

CSR starting kit, 35 µF, 20 µF, 98 µF

**8153013** **Connector, Solder Sleeve**

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)

**120Z0576** **Acoustic hood, Reciprocating**

Acoustic hood for two-cylinder compressor

**8156132** **Connector, GASKET**

Gasket, 1-3/4"

**120Z0762** **Mounting, Compressor kit**

Mounting kit 2 cylinder except HP

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**8168029** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)

**8168032** [🔗](#)**Connector, Rotolock service valve**

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)

**7703006** [🔗](#)**Connector, Valve set**

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")

**7701043** [🔗](#)**Electrical component, Starting kit**

CSR starting kit, 30 µF, 20 µF, 98 µF, 98 µF

**7754001** [🔗](#)**Lubricant, 160P**

Mineral oil, 160P, 2-litre can

**8173022** [🔗](#)**Electrical component, Relay**

Starting relay type RVA-6AMKL/3ARR3J4A4

**120Z0459** [🔗](#)**Crankcase heater, PTC heater**

PTC heater 27W, CE mark, UL

**7773107** [🔗](#)**Crankcase heater, Belt heater**

Belt type crankcase heater, 65 W, 230 V, CE mark, UL

**8156019** [🔗](#)**Connector, Sight glass**

Oil sight glass with gaskets (black and white)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT56HL1EVE

Spare Parts

**8156145** **Connector, GASKET**

Gasket for oil sight glass (black chloroprene)

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.