AGRICULTURE

Shaded Pole and PSC Direct Drive Fan 3.3" Diameter, Open and Totally Enclosed Designs


APPLICATIONS:

To meet manufacturer's requirements for fans and blowers.

FEATURES:

- Four 8-32 x 3/4" Stud Extensions At Each End
- Ball Bearings Have All Angle Thrust System
- Automatic Reset Thermal Overload Protector
- · Dual Studs
- · PSC Design With Capacitor Included
- 12" Leads
- · Discount Symbol: DS-3HAC





Open Air Over

HP	RPM	Voltage	Catalog Number	List	Enclosures	Rotation Shaft End	Amps	Shell Length	Shaft Dia. x Length *	Ship Wt. (lbs)	Notes
1/40	1550	115	3803	\$69	OAO	CW	2.0	3.40	0.25 x 2.00	5	
1/20	1550	115	9632	\$65	OAO	Rev	0.9	3.3	0.31 x 2.38	3	H38
1/12-1/20	1550	115/230	9664	\$111	OAO	Rev	1.3/0.7	4.2	0.31 x 2.5	5	H38
1/10	1550	115	9657	\$176	OAO	Rev	1.00	4.5	0.31 x 3.75	6	H28,H38

Totally Enclosed, Air Over

НР	RPM	Voltage	Catalog Number	List	Enclosures	Rotation Shaft End	Amps	Shell Length	Shaft Dia. x Length *	Ship Wt. (lbs)	Notes
1/50	1550	115	9624	\$63	TEAO	Rev	0.70	2.46	0.25 x 2.50	3	H38
	1550	115	9641	\$68	TEAO	Rev	0.50	3.1	0.25 x 2.25	5	H38
	1550	115	9642	\$68	TEAO	CW	0.70	2.5	0.25 x 2.25	2	
1/30	1550	115	9628	\$64	TEAO	Rev	1.20	3.00	0.31 x 2.50	3	

OEM Direct Replacements

НР	RPM	Voltage	Catalog Number	List	Enclosures	Rotation Shaft End	Amps	Shell Length	Shaft Dia. x Length *	Ship Wt. (lbs)	Notes	OEM
1/20	1550	115	9662	\$115	OAO	CCW/Rev	0.85	3.3	0.31 x 3.0	4	86,H30	ВО
	1550	208-230	9648	\$80	OAO	CW	0.4	3.3	0.31 x 2.25	3	H38	FE
	1550	115/230	9654	\$120	TEAO	CW	0.8/0.4	3.4	0.31 x 1.63	4	86,H31	KR
1/15	1550	208-230	9656	\$112	OAO	CCW/Rev	0.48	4.2	0.31 x 2.56	5	86,H30	ВО

BO = Bohn®†

FE = Fedders®†


KR = Krack®†

Note 86 **PSC** with Capacitor Note H28 Includes Hex Mounting Hub Both Ends Note H31 Note H38

Note H30

Includes Special Cord And Plug Includes Special Mounting Lugs, No Threaded Studs

PSC, Capacitor included and attached





^{*} As Measured From Motor Face