



115N0274

Optyma™, OP-HJZ022D39Q

Segment usage: Medium Back Pressure, Refrigerant: R134a; R404A; R448A; R449A; R452A; R513A, Compressor power supply [V/Ph/Hz]: 230/3/60

PRODUCT DETAILS

Gross weight	64 kg	
Net weight	55 kg	
Air flow @ 60Hz [m³/h]	2400 m³/h	
Applications	HBP MBP	
Compressor model	MTZ022-3	
Compressor power supply [V/Ph/Hz]	230/3/60	
Condenser type	D8	
Description	OP-HJZ022D39Q	
Electrical code	Q	
Fan current @ 60Hz [A]	1.1 A	
Fan diameter [mm]	355 mm	
Fan power consumption @ 60Hz [W]	285 W	
Fan power supply [V/Ph/Hz]	230/1/60	
Model number	OP-HJZ022D39Q	
No. of phases (compressor)	3	
No. of phases (fan)	1	
Number of fans	1	
Refrigerant	R134a R404A R448A R449A R452A R513A	
Segment usage	Medium Back Pressure	
Technology	Reciprocating	
Type	Optyma™	
Type designation	Condensing Units	
Version	D39	Optyma - Standard version for Brazil + full E-box

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



014L0022

SGP 10 l, Sight glass, FLARE, 10.00 mm, FLARE, 10.00 mm

Inlet connection type: FLARE, Inlet size [mm]: 10.00, Outlet connection type: FLARE, Outlet size [mm]: 10.00



023Z5040

Hermetic filter drier, DML, 08 cu.in., Steel

Inlet connection type: FLARE, Outlet connection type: FLARE, Core Size code: 08 cu.in.



061F6050

Cartridge pressure switch, ACB, 26.50 bar, 18.00 bar

Higher activ. pressure [bar]: 26.50, Lower activ. pressure [bar]: 18.00, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65



118U600908

Condensing Units Accessories & Spare parts : Receiver

Receiver 4L



120Z0459

Compressors Accessories : PTC heater

PTC heater 27W



120Z0638

Compressors Accessories : 175PZ

POE lubricant, 175PZ, 1-litre can



191U006010

Condensing Units Accessories & Spare parts : Miscellaneous

Suction Accumulator, ASD015H04 1/2 in



191U007610

Condensing Units Accessories & Spare parts : Oil Separator

Oil Separator, Hermetic OSD020H04 1/2in



191U127367

Condensing Units Accessories & Spare parts : Kit housing

Housing, D8 Optyma™ Line

For more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts**191U9905** **Condensing Units Accessories & Spare parts : Filter**

Basket Filter, 14 X 28MM APC-982 1 in

**6804500V01** **Condensing Units Accessories & Spare parts : Service Valve**

Rotalock valve V01 1Rx3/8S 38058 R

Image
coming
soon**6804501V06** **Condensing Units Accessories & Spare parts : Service Valve**

Rotalock valve V06 1-14R X 1/2 S

**MTZ22-3VI** **Reciprocating compressor, MTZ22JC3BVE**

Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A, Segment usage:

Refrigeration MT, Compressor power supply [V/Ph/Hz]: 200-230/3/60

**193U8024E** **Condensing Units Accessories & Spare parts**

MCHE + Packing D8 M19-22

For more information, please use this link to visit the product page on Danfoss Product Store 

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.