

**114N2321** **OP-UCHC0033UWC000B**

Segment usage: Low Back Pressure; Universal; Medium Back Pressure,
Refrigerants: R404A; R507A, Compressor power supply [V]: 115/1/60

PRODUCT DETAILS

Gross weight	22.14 Kg
Net weight	20.5 Kg
EAN	5702428390873
Air flow @ 60Hz [m ³ /h]	590 m ³ /h
Applications	HBP
	LBP
	MBP
Approval	UL listed
Compressor model	NF7CLX
Compressor power supply [V]	115/1/60
Condenser type	BM71
Description	OP-UCHC0033UWC000B
Electrical code	B
Family	Optyma™
Fan blade size [mm]	229 mm
Fan current @ 60Hz [A]	0.45 A
Fan power consumption @ 60Hz [W]	36 W
Fan power output @ 60Hz [W]	9 W
Fan power supply [V/Ph/Hz]	115/1/60
Fan voltage @ 60Hz (max) [V] [Max]	115 V
Fan voltage @ 60Hz (max) [V] [Min]	115 V
Frequency [Hz]	60 Hz
High value of nominal voltage at 60Hz [V]	127 V
In scope of WEEE and contain batteries	No
Length [mm]	432 mm
Liquid line connection [in]	1/4 in
Low value of nominal voltage at 60Hz [V]	115 V
Model number	OP-UCHC0033UWC000B
No. of phases (compressor)	1
No. of phases (fan)	1
Number of fans	1
Phase	1
Phases of Compressor	1
Phases of Fan	1
Product group	Condensing Units
Product Name Description	Bare unit

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.





Product Detail | OP-UCHC0033UWC000B

PRODUCT DETAILS

REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Receiver approval	UL
Receiver volume [L]	0.8 L
Refrigerants	R404A R507A
Region	North America
RLA	56 A
Segment usage	Low Back Pressure Medium Back Pressure Universal
Suction connection size [in]	3/8 in
Technology	Reciprocating
Total height [mm]	259 mm
Type	Optyma™ WB
Version	WB
Voltage 60Hz [V]	115 V
Voltage 60Hz [V] [Max]	127 V
Width [mm]	330 mm
Proposition 65	WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

	119-5669 ↗ Fan system, Fan blade Fan blade
	119-5662 ↗ Fan system, Fan motor Fan motor 9W 115V/60Hz
	119-7768 ↗ Electrical component, Capacitor Start capacitor 320µF, 125V - NF,TF
	119-7761 ↗ Electrical component, Starting relay Relay HST

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Accessories

**117U4129** [🔗](#)**Electrical component, Relay**

SML. RELC, HST - "MRT22AFZ-6;117U2101

Image
coming
soon**119-3256** [🔗](#)**Fan system, Fan motor**Fan motor

Spare Parts

**119-2304** [🔗](#)**Condensing Units Accessories & Spare parts, Compressor**NF7CLX

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.