

**114N2331****OP-HCHC0075UWC000N**

Segment usage: Medium Back Pressure, Refrigerants: R404A; R507A, Compressor power supply [V]: 230/1/60



PRODUCT DETAILS

| | |
|---|--------------------------|
| Gross weight | 41.4 Kg |
| Net weight | 38.5 Kg |
| EAN | 5702428390774 |
| Air flow @ 60Hz [m ³ /h] | 1480 m ³ /h |
| Applications | MBP |
| Approval | UL listed |
| Approval file name | 52L3 |
| Compressor model | T6220GK2 |
| Compressor power supply [V] | 230/1/60 |
| Condenser type | BM81 |
| Description | OP-HCHC0075UWC000N |
| Electrical code | N |
| Family | Optyma™ |
| Fan blade size [mm] | 305 mm |
| Fan current @ 60Hz [A] | 1 A |
| Fan power consumption @ 60Hz [W] | 150 W |
| Fan power output @ 60Hz [W] | 50 W |
| Fan power supply [V/Ph/Hz] | 230/1/60 |
| Fan voltage @ 60Hz (max) [V] [Max] | 230 V |
| Fan voltage @ 60Hz (max) [V] [Min] | 230 V |
| Frequency [Hz] | 60 Hz |
| High value of nominal voltage at 60Hz [V] | 230 V |
| In scope of WEEE and contain batteries | No |
| Length [mm] | 483 mm |
| Liquid line connection [in] | 1/4 in |
| Low value of voltage range at 60Hz [V] | 208 V |
| Model number | OP-HCHC0075UWC000N |
| No. of phases (compressor) | 1 |
| No. of phases (fan) | 1 |
| Number of fans | 1 |
| Phase | 1 |
| Phases of Compressor | 1 |
| Phases of Fan | 1 |
| Product group | Condensing Units |
| Product Name Description | Bare unit |
| REACH Candidate List substances | Lead (CAS no. 7439-92-1) |
| Receiver approval | UL |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

| | |
|------------------------------|---|
| PRODUCT DETAILS | |
| Receiver volume [L] | 1.7 L |
| Refrigerants | R404A |
| | R507A |
| Region | North America |
| Segment usage | Medium Back Pressure |
| Speed Platform | Fixed-speed |
| Suction connection size [in] | 3/8 in |
| Technology | Reciprocating |
| Total height [mm] | 340 mm |
| Type | Optyma™ WC |
| Version | WC |
| Voltage 60Hz [V] | 208 V |
| Voltage 60Hz [V] [Max] | 230 V |
| Width [mm] | 429 mm |
| Proposition 65 | WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

| | |
|---|---|
| Accessories | |
|  | 119-5674 ↗ |
| | Fan system, Fan blade Fan blade |
|  | 119-5659 ↗ |
| | Fan system, Fan motor Fan motor 208-230V/50-60Hz |

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.