



014L0009

SGP 12 I, Sight glass, Flare, 12.00 mm, Flare, 12.00 mm

Inlet connection type: Flare, Inlet size [mm]: 12.00, Outlet connection type: Flare, Outlet size [mm]: 12.00

PRODUCT DETAILS

Gross weight	0.257 Kg
Net weight	0.207 Kg
Volume	0.155 Liter
EAN	5702428840712
Approval	C UL US LISTED EAC
Approval file name	REF. LIQUID INDICATOR 76H4
Body material	Brass
China RoHS compliance	Yes exceed limitations
Connection material	Brass
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(c)
Green: max moist con@25 °C	R22: 150 ppm
Green: max moist con@43 °C	R22: 250 ppm
In scope of WEEE and contain batteries	No
Inlet connection type	Flare
Inlet Internal/External	External
Inlet size [in]	1/2 in
Inlet size [mm]	12 mm
Max. Working Pressure [bar]	52 bar
Max. Working Pressure [psig]	754 psig
Moisture indicator	Indicator
Other RoHS documentation	Saudi Arabia RoHS
Outlet connection type	Flare
Outlet Internal/External	External
Outlet size [in]	1/2 in
Outlet size [mm]	12 mm
Packing format	Multi pack
Product accessories	Generic accessories
Product group	Sight glasses
Product Name Description	Sight glass
Quantity per packing format	25 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1) Cobalt dichloride (CAS no. 7646-79-9)
Refrigerants	R22
SCIP dossier no.	323c7b85-ff73-43cd-8fce-a44eabbf5297
Serviceable	No

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.

PRODUCT DETAILS

Temperature range [°C] [max]	80 °C
Temperature range [°C] [min]	-50 °C
Temperature range [°F] [max]	175 °F
Temperature range [°F] [min]	-58 °F
Type	SGP 12 I
UK RoHS compliance	Out of scope
UL approval file name	REF. LIQUID INDICATOR 76H4
UL approved refrigerants	R22
Yellow: min moist con@25 °C	R22: 300 ppm
Yellow: min moist con@43 °C	R22: 500 ppm

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)