

**060H1708** **Thermostat, UT 72**

Temperature range [°C]: -30 - 30, Reset function: Auto, Contact function: SPDT,
Capillary tube length [mm]: 3000, Enclosure rating IP: IP20

PRODUCT DETAILS

| | |
|---|--|
| Gross weight | 0.246 Kilogram |
| Net weight | 0.094 Kilogram |
| Volume | 1.119 Liter |
| EAN | 5702428567145 |
| Ambient temperature range [°C] [max] | 55 °C |
| Ambient temperature range [°C] [min] | -30 °C |
| Ambient temperature range [°F] [max] | 130 °F |
| Ambient temperature range [°F] [min] | -22 °F |
| Approval | CE EAC EMCD LVD RoHS RoHS China TYSK UKCA |
| Capillary tube length [mm] | 3000 mm |
| Capillary tube material | Copper |
| China RoHS compliance | Yes |
| Contact function | SPDT |
| Contact rating | AC15=1 A, 250 V AC1=16 A, 250 V AC3=7,5 A, 250 V |
| Differential (FS) [K] | 3 K |
| Electrical connection | Clamps Terminal screws |
| Enclosure rating IP | IP20 |
| EU RoHS compliance | Yes |
| EU RoHS exemption clause | No |
| Further information | Fahrenheit scale |
| In scope of WEEE and contain batteries | No |
| Max. sensor temperature [°C] | 80 °C |
| Max. sensor temperature [°F] | 176 °F |
| Mounting method | Wall |
| Packing format | Multi pack |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Thermostat, UT 72**PRODUCT DETAILS**

| | |
|-------------------------------------|--------------------------|
| Product accessories | Switches accessories |
| Product group | Switches and thermostats |
| Product Name Description | Thermostat |
| Quantity per packing format | 24 pc |
| Reset function | Auto |
| Sensor size (Ø x L) [in] | 15/64 x 4 44/64 in |
| Sensor size (Ø x L) [mm] | 6 x 119 mm |
| Serviceable | No |
| Temperature range [°C] [max] | 30 °C |
| Temperature range [°C] [min] | -30 °C |
| Temperature range [°F] [max] | 85 °F |
| Temperature range [°F] [min] | -22 °F |
| Type | UT 72 |
| UK RoHS compliance | Yes |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)