

**115N0290****Optyma™, OP-HJZ040D39Q**

Segment usage: Medium Back Pressure, Refrigerant: R134a; R404A; R448A; R449A; R452A; R513A, Compressor power supply [V/Ph/Hz]: 230/3/60

PRODUCT DETAILS

Gross weight	95 kg	
Net weight	82 kg	
Air flow @ 60Hz [m³/h]	6300 m³/h	
Applications	HBP MBP	
Compressor model	MTZ040-3	
Compressor power supply [V/Ph/Hz]	230/3/60	
Condenser type	J8	
Description	OP-HJZ040D39Q	
Electrical code	Q	
Fan current @ 60Hz [A]	2.6 A	
Fan diameter [mm]	457 mm	
Fan power consumption @ 60Hz [W]	889 W	
Fan power supply [V/Ph/Hz]	230/1/60	
Model number	OP-HJZ040D39Q	
No. of phases (compressor)	3	
No. of phases (fan)	1	
Number of fans	1	
Refrigerant	R134a R404A R448A R449A R452A R513A	
Segment usage	Medium Back Pressure	
Technology	Reciprocating	
Type	Optyma™	
Type designation	Condensing Units	
Version	D39	Optyma - Standard version for Brazil + full E-box

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**014L0025** [🔗](#)**SGP 12 I, Sight glass, FLARE, 12.00 mm, FLARE, 12.00 mm**

Inlet connection type: FLARE, Inlet size [mm]: 12.00, Outlet connection type: FLARE, Outlet size [mm]: 12.00

**023Z5044** [🔗](#)**Hermetic filter drier, DML, 16 cu.in., Steel**

Inlet connection type: FLARE, Outlet connection type: FLARE, Core Size code: 16 cu.in.

**061F6050** [🔗](#)**Cartridge pressure switch, ACB, 26.50 bar, 18.00 bar**

Higher activ. pressure [bar]: 26.50, Lower activ. pressure [bar]: 18.00, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65

**118U601108** [🔗](#)**Condensing Units Accessories & Spare parts : Receiver**

Receiver 8L

**120Z0459** [🔗](#)**Compressors Accessories : PTC heater**

PTC heater 27W

**120Z0638** [🔗](#)**Compressors Accessories : 175PZ**

POE lubricant, 175PZ, 1-litre can

**191U006110** [🔗](#)**Condensing Units Accessories & Spare parts : Miscellaneous**

Suction Accumulator, ASD020H05 5/8 in

**191U007710** [🔗](#)**Condensing Units Accessories & Spare parts : Oil Separator**

Oil Separator, Hermetic OSD025H05 5/8in

Image
coming
soon

191U0644E [🔗](#)**Condensing Units Accessories & Spare parts**

MCHE + Shroud J8 Hj40-64 Lj136

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**191U127667** [🔗](#)**Condensing Units Accessories & Spare parts : Kit housing**

Housing, J8 Optyma™ Line

**191U9906** [🔗](#)**Condensing Units Accessories & Spare parts : Filter**

Basket Filter, 22 X 28MM APC-983 1 1/4 in

Image
coming
soon**6804501V06** [🔗](#)**Condensing Units Accessories & Spare parts : Service Valve**

Rotalock valve V06 1-14R X 1/2 S

Image
coming
soon**6804502V09** [🔗](#)**Condensing Units Accessories & Spare parts : Service Valve**

Rotalock valve V09 1 1/4-12R X 5/8 S

**MTZ40-3VI** [🔗](#)**Reciprocating compressor, MTZ40JH3AVE**

Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A, Segment usage:

Refrigeration MT, Compressor power supply [V/Ph/Hz]: 200-230/3/60

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.